



TECHNICAL DATA SHEET

GLOSS - Floor Finish High Gloss, Durable and Slip Resistant

Code: REGL



Resistol Gloss Floor Finish produces a high gloss while protecting the floor under the toughest conditions. Responds well to high speed burnishing and is excellent for high traffic areas.

DIRECTIONS FOR USE:

Preparation: Blockade area until floor finish is dry as floors will be very slippery during the preparation and application of the finish. Scrub or Strip floor thoroughly using CHEMOTEC or SAFEBLEND brand products. Pick up stripped finish before it dries using a wet vacuum, a clean mop or autoscrubber. Rinse with liberal amounts of cold clean water until all residues have been eliminated. Allow floor to dry completely before applying RESISTOL GLOSS. **Application:** For best results, use a clean floor finish mop and clean bucket (or use liner in bucket) and wringer. Pour floor finish into bucket, saturate mop with RESISTOL GLOSS. Press mop firmly into wringer to remove excess product but do not wring mop. Apply RESISTOL GLOSS in even coats. Allow each coat to dry. Drying time is approximately 30 minutes. (Drying time may vary depending on temperature, humidity, ventilation and thickness of each coat). Apply 3 - 4 coats or until desired gloss is achieved. Never apply more than 4 coats per 24-hour period. **Coverage:** Approximately 2000 square feet per 4 litres. **Maintenance:** Dust mop. Clean floor as needed using a CHEMOTEC or SAFEBLEND neutral cleaner. Burnish using appropriate pads.

NOTE: Do not pour unused floor finish back into container. Do not let product spoil food, feed or potable water during use. Do not use on food contact surfaces. The amount of product used should not be in excess of that required to achieve its intended technical effect.

STORAGE: Keep in a tightly sealed container in a well-ventilated room. Do not store on surfaces that may come into contact with food products. Keep from freezing.

PHYSICAL PROPERTIES	WHIMIS Class: D2B	CFIA: Accepted
Boiling Point: 100°C	Vapor pressure: (mm Hg): N/A	
Specific Gravity (H₂O =1): 1.03 at 20°C	Evaporation Rate: (Water = 1): 1	
% Non-volatile Solids: 23 % Brix Solids: 25	Flash point: > 93°C	
Solubility in Water: Miscible	TDG Classification: Not regulated	
pH (as supplied): 8-7	Physical State: Liquid	
Odour Threshold (ppm): N/A	Viscosity: < 100 cps at 25°C	
Appearance and Odour: White liquid, characteristic odour	Slip Coefficient: > 0.5 (ASTM D 2047)	

Please Recycle

● All of our containers are fully recyclable
● Our boxes contain at least 50% recycled fibre
● Our labels use FDA approved vegetable based ink



8820, Place Ray Lawson, Anjou, Québec, Canada H1J 1Z2
Tel 514.729.6321 • 800.729.6321
Fax 514.729.6322
service@safblend.com www.safblend.com

For more information, please visit
www.chemotec.ca

