

TECHNICAL DATA SHEET



Defoamer

Code: ANFO



Resistol Defoamer is a concentrated defoaming formulation that reduces and eliminates unwanted or excessive foam in recovery tanks, automatic scrubbers, shampooing machines, and carpet extractors.

DIRECTIONS FOR USE:

CARPET EXTRACTORS: Prior to using extractor, add 30-60 mL of RESISTOL DEFOAMER in recovery tank. For best results, dilute 30 mL of RESISTOL DEFOAMER in one litre of cold water and use vacuum hose to pick up solution into recovery tank; this allows all surfaces of the machine to get coated with defoamer, increasing efficiency. **AUTOMATIC FLOOR SCRUBBERS AND WET-VAC:** Prior to picking up stripper and emulsified floor finish pour RESISTOL DEFOAMER (50-150 mL) in front of the machine and pick it up with scrubber or Wet-Dry Vac; this allows all surfaces of the machine to get coated with defoamer.

STORAGE: Keep in a tightly sealed opaque container away from sunshine in a well-ventilated room. Do not store on surfaces that may come into contact with food products. Keep from freezing.

PHYSICAL PROPERTIES

Boiling Point: 100°C

Specific Gravity (H₂O =1): 1.00 at 20°C

% Volatile (Wt%): <1

Solubility in Water: Miscible

pH (as supplied): 7,0-8,0

Odour Threshold (ppm) : N/A

Appearance and Odour: White liquid, Light odour

GHS: skin irritant category 2 and an eye irritant category 2

CFIA: Accepted

Vapor pressure: (mm Hg): N/A

Vapor Density: (Air=1): N/A

Evaporation Rate: (Water = 1): 1

Flash point: None

TDG Classification: Not regulated

Physical State: Liquid

Viscosity: Approx. 1,000-1,400 cps at 25°C

Please Recycle

- All of our containers are fully recyclable
- Our boxes contain at least 50% recycled fibre
- Our labels use FDA approved vegetable based ink



8820, Place Ray Lawson, Anjou, Québec, Canada H1J 1Z2
Tel 514.729.6321 • 800.729.6321
Fax 514.729.6322
service@safblend.com www.safblend.com

For more information, please visit
www.chemotec.ca

