



## HIGH GLOSS, DURABLE AND SLIP RESISTANT

### TECHNICAL DATA SHEET

CODE : RE18

#### DESCRIPTION:

**Resistol 18** is specially formulated to provide a durable, high-gloss floor finish after every job. It excels in durability and resistance to black heel scuffs, slips and powdering. The natural colours of all floor surfaces are enhanced by RESISTOL floor care products. To obtain a wet-look appearance, use a high-speed buffing machine.

#### DIRECTIONS FOR USE:

**Preparation:** Blockade area until floor finish is dry as floors will be very slippery during the preparation and application of the finish. Scrub or Strip floor thoroughly using CHEMOTEC or SAFEBLEND brand products. Pick up stripped finish before it dries using a wet vacuum, a clean mop or autoscrubber. Rinse with liberal amounts of cold clean water until all residues

have been eliminated. Allow floor to dry completely before applying RESISTOL 18. **Application:** For best results, use a clean floor finish mop and clean bucket (or use liner in bucket) and wringer. Pour floor finish into bucket, saturate mop with RESISTOL 18. Press mop firmly into wringer to remove excess product but do not wring mop. Apply RESISTOL 18 in even coats. Allow each coat to dry. Drying time is approximately 30 minutes. (Drying time may vary depending on temperature, humidity, ventilation and thickness of each coat). Apply 3 - 4 coats or until desired gloss is achieved. Never apply more than 4 coats per 24-hour period. **Coverage:** Approximately 2000 square feet per 4 litres. Maintenance: Dust mop. Clean floor as needed using a CHEMOTEC or SAFEBLEND neutral cleaner. Burnish using appropriate pads.

**NOTE:** Do not pour unused floor finish back into container. Do not let product spoil food, feed or potable water during use. Do not use on food contact surfaces. The amount of product used should not be in excess of that required to achieve its intended technical effect.

**STORAGE:** Keep in a tightly sealed container in a well-ventilated room. Do not store on surfaces that may come into contact with food products. Keep from freezing.

PHYSICAL PROPERTIES:	
Boiling Point :	100°C
Specific Gravity (H2O = 1) :	1.02 to 20°C
% Non-volatile Solids :	15
% Brix Solids:	18
Solubility in Water :	Miscible
pH (as supplied) :	8-9
Odour Threshold	N/A
Apparence and Odour:	White liquid, characteristic odour

WHIMIS Class: D2B	ACIA: Accepted
Vapor pressure: (mm Hg):	N/A
Evaporation Rate: (Water = 1)	1
Flash point:	>93°C
Physical State	Liquid
Viscosité:	<100 cps at 24°C
TDG Classification:	Not regulated
Slip Coefficient:	>0.5 (ASTM D 2047)



**CHEMOTEC**

8820, Place Ray Lawson, Anjou, Québec H1J 1Z2  
 Tel 514.729.6321 • 800.729.6321 • Fax 514.729.6322  
 service@safblend.ca • www.safblend.ca