



HIGH GLOSS, DURABLE AND SLIP RESISTANT

TECHNICAL DATA SHEET

CODE : RE18

DESCRIPTION:

This high-quality Floor Finish is specially formulated to provide a durable, high-gloss floor finish after every job. It excels in durability and black heel scuffs, slip and powdering resistance. The natural colours of all floor surfaces are enhanced by RESISTOL floor care products. To obtain a "wet-look" appearance, use a high-speed buffing machine with. **18% SOLIDS – ULTRA HIGHT GLOSS, BUFFABLE, EXTRA DURABLE, SLIP**

DIRECTIONS:

FOR BEST RESULTS: Follow these procedures:



STRIPPING: Remove all previous coatings with RESISTOL STRIPPER. Rinse well with water.

APPLICATION: Apply even coats of RESISTOL 18 floor finish with a clean damp mop. Allow proper drying time between coats according to ventilation and room temperature.

MAINTENANCE: Clean with RESISTOL ND-50 Neutral Detergent.

IMPORTANT: Do not pour unused materials into the original container.

NOTE: Surfaces subject to direct food contact must be thoroughly rinsed with potable water.

STORAGE: Keep in a tightly sealed container, in a well-ventilated room at room temperature. Keep from freezing.

PHYSICAL PROPERTIES:	
Boiling Point :	100°C
Specific Gravity (H2O = 1) :	1.018 to 20°C
Vapor Pressure	(mm Hg): 16-16
% Non-volatile Solids :	15-16
Vapor Density	(Air=1): N/A
Evaporation Rate	(Water=1): 1
Solubility in Water :	Dispersible
pH (as supplied) :	7.5-9.0
Physical State	Liquid
Viscosité:	<100 cps at 25°C
Apparence and Odour:	White liquid, Acrylic odour
Odour Threshold (ppm)	N/A

WHIMIS Class:	Skin irritation- Category 2. Eye irritation- Category 2
TDG Classification:	Not regulated



CHEMOTEC

5800 Ontario E., Montreal, Qc, Canada H1N 0A2
Tel 514.729.6321 • 800.729.6321 • Fax 514.729.6322
service@safblend.ca • www.safblend.ca